

>B< MaxiPro Refrigerant Compatibility Table

A1

Refrigerant	GWP*	Safety Group	Compatible
R-125	3500	A1	✓
R-134a	1430	A1	✓
R-404A	3922	A1	✓
R-407A	2107	A1	✓
R-407C	1744	A1	✓
R-407F	1825	A1	✓
R-407H	1495	A1	✓
R-410A	2088	A1	✓
R-417A	2346	A1	✓
R-421A	2631	A1	✓
R-422B	2526	A1	✓
R-422D	2729	A1	✓
R-427A	2138	A1	✓
R-438A	2264	A1	✓
R-448A	1386	A1	✓
R-449A	1397	A1	✓
R-450A	601	A1	✓
R-452A	2140	A1	✓
R-452C	2220	A1	✓
R-507A	3985	A1	✓
R-513A	631	A1	✓
R-513B	596	A1	✓
R-515B	299	A1	✓
R-718	0	A1	✓
R-424A	2240	A1	✓
R-434A	3245	A1	✓
R-437A	1805	A1	✓
R-453A	1640	A1	✓
R-456A	687	A1	✓
R-513	573	A1	✓
Ethylene Glycol	-	A1	✓

Air Conditioning and Refrigeration

A2L

Refrigerant	GWP*	Safety Group	Compatible
R-454B**	466	A2L	✓
R-1234ze**	7	A2L	✓
R-32**	675	A2L	✓
R-444A**	92	A2L	✓
R-447A**	582	A2L	✓
R-447B**	740	A2L	✓
R-452B**	698	A2L	✓
R-454A**	239	A2L	✓
R-454C**	148	A2L	✓
R-457A**	139	A2L	✓
R-459A**	460	A2L	✓
R-1234yf**	4	A2L	✓

A3

Refrigerant	GWP*	Safety Group	Compatible
R-290**	3	A3	✓
R-600A**	3	A3	✓

Note: >B< MaxiPro fittings are **NOT** suitable for R-717, R-723, R-764, R-744, R-22 refrigerants.

** When using refrigerants classified A2L (lower flammability), A2 (flammable) and A3 (higher flammability) additional/specific standards, local rules and regulations, codes of practice and by-laws may be applicable.